

5

10 The present invention relates in a general way to the progressive decoding of digital data coded with at least one region of interest. These digital data are digital images. The invention relates more particularly to alerting during this progressive decoding.

15 The most recent methods for compressing images make it possible to code an image in a progressive way in terms of quality. The decoding of this image is also progressive, and it is possible to display a part of the image, or a low-quality version thereof, before the entire image has been decoded. In step with the decoding of the supplementary data, the quality of the image displayed is enhanced. This possibility is especially advantageous during the transmission
20 of the coded image, since, upon reception, the operations of receiving, decoding and display are performed in a progressive way.

 Moreover, it is possible to define a region of interest in the image. A region of interest is composed of one or more parts of the image. The region of interest is defined by a user and will be coded with a higher quality by comparison with the rest of the image.
25

 The standard JPEG2000 (in the course of standardisation) allows the two functionalities to be implemented.

 In this context, the present invention aims to supply an indication during the progressive decoding of an image coded with a region of interest, in
30 such a way as to indicate to a user the end of the decoding of the region of interest.

To that end, the invention proposes a method for alerting during the progressive decoding of a digital image coded with a region of interest, characterised in that it includes the stages of:

- detection of the end of the decoding of the said region of interest,
- 5 - activation of an indication of the end of decoding of the said region of interest.

Correspondingly, the invention relates to a device for alerting during the progressive decoding of a digital image coded with a region of interest, characterised in that it includes:

- 10 - means for detecting the end of the decoding of the said region of interest,
- means for activating an indication of the end of decoding of the said region of interest.

By virtue of the invention, the user knows that the region of interest
15 has been completely received; he can start his interpretation thereof, or interrupt the decoding if the rest of the image is not of interest to him.

According to one preferred characteristic, the method further includes the stages of:

- 20 - activation of an indication of the start of decoding of the said region of interest,
- activation of an indication of the progress of the decoding of the said region of interest.

Thus the user is in a position to follow the progress of the decoding of the region of interest.

25 According to another preferred characteristic, the method further includes the stage of decoding of the coded data of the image which are not in the said region of interest.

According to another preferred characteristic, the method further includes the stages of:

- 30 - activation of an indication of decoding of the coded data of the image which are not in the said region of interest,

- activation of an indication of the end of decoding of the coded data of the image which are not in the said region of interest.

Thus the user knows the progress of the decoding of the entire image.

5 According to one preferred characteristic, the indication is a display of information data on a screen.

Such information is simple to perceive for the user.

The alerting device includes means for implementing the preceding characteristics.

10 The invention also relates to a method and a device for receiving data incorporating the alerting method presented above.

The invention further relates to a method and a device for progressive decoding of a digital image coded with a region of interest, incorporating the alerting method presented above.

15 The invention also relates to a digital apparatus including the alerting, decoding or receiving device, or means for implementing the alerting, decoding or receiving method. The advantages of the device and of the digital apparatus are identical to those set out above.

20 An information storage means, which can be read by a computer or by a microprocessor, integrated into the device or otherwise, possibly removable, stores in memory a program implementing the alerting, receiving or decoding method.

25 The characteristics and advantages of the present invention will emerge more clearly on reading a preferred embodiment illustrated by the attached drawings, in which:

- Figure 1 is an embodiment of a device implementing the invention,
- Figure 2 represents a coding device and a decoding device according to the invention,
- Figure 3 represents a frequency sub-band obtained in the coding
- 30 device
- Figure 4 is a bit plane representation of a digital signal,

- Figure 5 is a bit plane representation of a digital signal, in which a region of interest has been boosted,

- Figure 6 represents an implementation of the coding method,

5 - Figure 7 represents an embodiment of a device according to the invention,

- Figure 8 represents an implementation of the decoding method according to the invention,

- Figure 9 represents a display area for decoded data according to the invention,

10 - Figure 10 is a bit plane representation of a digital signal in which a region of interest has been boosted.

According to the embodiment chosen and represented in Figure 1, a device implementing the invention is, for example, a microcomputer 10 connected to various peripherals, for example a digital camera 107 (or a scanner,
15 or any image acquisition or storage means) connected to a graphics card and supplying information to be processed according to the invention.

The device 10 includes a communications interface 112 linked to a network 113 able to transport digital data to be processed, or conversely data processed by the device. The device 10 also includes a storage means 108
20 such as a hard disk, for example. It also includes a disk 110 drive 109. This disk 110 may be a diskette, a CD-ROM or a DVD-ROM, for example. The disk 110, like the disk 108, may contain data processed according to the invention as well as the program or programs implementing the invention which, once read by the device 10, will be stored on the hard disk 108. According to one variant, the
25 program allowing the device to implement the invention could be stored in read-only memory 102 (called ROM on the drawing). In a second variant, the program could be received so as to be stored in a way identical to that described above by means of the communications network 113.

The device 10 is linked to a microphone 111. The data to be processed
30 according to the invention will be from the audio signal, in this case.

This same device possesses a screen 104 making it possible to view the data to be processed or to serve as interface with the user who can thus set

parameters for certain processing modes, by the use of the keyboard 114 or of any other means (mouse, for example).

The central processing unit 100 (called CPU on the drawing) executes the instructions relating to the implementing of the invention, instructions
5 stored in the read-only memory 102 or in the other storage elements. When voltage is applied, the processing programs stored in a non-volatile memory, for example the ROM 102, are transferred into the random-access memory RAM 103 which will then contain the executable code of the invention as well as registers for storing the variables necessary for implementing the invention.

10 More generally, an information-storage means, which can be read by a computer or by a microprocessor, incorporated into the device or otherwise, possibly removable, stores a program implementing the method of coding, of transmission and, respectively, of decoding.

The communications bus 101 allows communication between the
15 various elements included in the microcomputer 10 or linked to it. The representation of the bus 101 is not a limitation, and the central processing unit 100 especially is capable of communicating instructions to any element of the microcomputer 10 directly or via another element of the microcomputer 10.

With reference to Figure 2, an embodiment of a coding device and of
20 an associated decoding device according to the invention is more particularly intended to process digital images.

A signal source 1 contains a fixed-image signal IM. In a general way, the signal source either contains the digital signal, and, for example, includes a memory, a hard disk or a CD-ROM, or converts an analogue signal into a digital
25 signal, and is, for example, an analogue video recorder associated with an analogue-digital converter. The image source 1 generates a series of digital samples representing an image IM. The image signal IM is a series of digital words, for example of bytes. Each byte value represents one pixel of the image IM, here with 256 grey levels or in colour.

30 An output from the signal source 1 is linked to a data-compression circuit 2 which carries out coding of the image, known in itself. For example, the coding used is according to the standard JPEG2000 (for Joint Photographic Ex-

pert Group), which is in the course of standardisation and a description of which is available by Internet at the address <http://www.jpeg.org/cd15444-1.pdf>.

Coding according to the JPEG2000 standard includes a discrete-wavelet transformation, known as DWT, then quantization and entropic coding.

5 On completion of the wavelet transformation, the data are processed by bit plane. As represented in Figure 3, a frequency sub-band obtained after wavelet transformation includes $P \times Q$ coefficients, where P and Q are integers. Each coefficient includes a sign bit and M amplitude bits numbered from 0 in the case of the least significant bit up to the $M-1$ in the case of the most significant bit,
10 where M is an integer.

The sub-band can therefore be seen as a plane containing $P \times Q$ sign bits and M planes each containing $P \times Q$ bits.

By reference again to Figure 2, the data-coding circuit 2 is linked to a data-transmission circuit 3. The circuit 3 is conventional and is suitable for
15 transmitting data intended for a receiving circuit 4, via a transmission network.

The circuit 4 is linked to the data-decoding circuit 5, itself linked to a circuit 6 for viewing the decoded data.

The operation of the coding device and of the decoding device will be detailed in what follows.

20 Figure 4 represents an example representation, by bit planes, in a one-dimensional case. This case is, for example, a line of data extracted from a frequency sub-band of the image.

Plane number zero contains the least significant bits and the planes are sequenced in such a way as to contain bits of higher and higher significance
25 in proportion as the numbers of the planes increase. Hence, plane number 14 contain the most significant bits.

In this example, it is observed that the most significant bit plane containing at least one bit at the value one is plane number five.

Moreover, a boost value B is defined as a function of several pa-
30 rameters, particularly including the type of wavelet transformation used.

The boost value is higher than or equal to the highest-numbered bit plane containing at least one non-zero bit for all the sub-bands of the signal. This bit plane is the highest bit plane reached by the signal.

For example, for an image coded over eight bits (i.e. up to plane number 7), a wavelet transformation is considered in which the filter multiplies the dynamic range of the signal by 4 (2 in vertical filtering and 2 in horizontal filtering). The highest bit plane reached after transformation is then plane number 9, since multiplication of the dynamic range by 4 requires 2 additional bits for coding.

Figure 5 represents the same data as in Figure 4, to which a boost value equal to 9 has been applied over a region of interest ROI. A region of interest is a part of the image to which the user accords greater importance than the rest of the image. For example, a region of interest is a face in a portrait, or the fractured part of a bone in an x-ray. It should be noted that the region of interest may be formed from several disjointed parts of the image.

The data associated with the region of interest are transferred 9 bit planes higher.

It should be noted that it is not necessary to associate information to indicate which is the region of interest, especially during the transmission of the data. This is because, in order to recover the region of interest during the decoding of the data, it is sufficient to detect the coefficients for which non-zero bits exist in the bit planes numbered higher than or equal to 9.

These data have necessarily been boosted, since the signal does not naturally reach this dynamic range.

During decoding, it is sufficient then to transfer these data nine bit planes lower in order to obtain the decoded signal.

Figure 6 represents a method of coding an image with a region of interest. This method is employed in the coding device of Figure 1 and includes stages E1 to E3.

The method is implemented in the form of an algorithm which can be wholly or partly stored in memory in any information-storage means capable of working with the microprocessor. This storage means can be read by a com-

puter or by a microprocessor. This storage means is or is not integrated into the device, and may be removable. For example, it may include a magnetic tape, a diskette or a CD-ROM (compact disc with fixed memory).

Stage E1 is the definition of a region of interest in the image. To do that, a window for each part of the region of interest can be designated by using the mouse, on the image displayed on the screen. Each part of the region of interest may also be defined by entering its coordinates using the keyboard.

The following stage E2 is a coding of the image with progressive quality (or "quality scalable"). Thus, the data contained in the compressed file are organised in such a way that the most important data are at the start of the file. The most important data are understood here to be the bit planes of most significance.

The coding includes operations of boosting a region of interest, in addition to the conventional operations which are not described here.

It should be noted that the boost value B is associated with the compressed file containing the result of the coding of the image.

The following stage E3 is a progressive transmission of the data. The most important data are transmitted first. Hence, on reception, the most important data are received first, and can be processed before the rest of the data. In particular, the most important data can be decoded and displayed, in the case of an image signal, before all the data have been received.

As represented in Figure 7, one embodiment of the implementation of the invention includes a computer 7, which can be connected to a remote database 8, via a telecommunications network 9.

The database 8 contains data coded as described above. These data are images, more particularly.

Figure 8 represents an implementation of the alerting method which is performed during the progressive decoding of the previously coded image. This method is implemented in the form of an algorithm stored in memory of the computer 7. It is run in parallel with the receiving and with the decoding of the image, which are not described in detail here.

The method can be wholly or partly stored in memory in any information-storage means capable of working with the microprocessor of the computer. This storage means is or is not integrated into the device, and may be removable. For example, it may include a magnetic tape, a diskette or a CD-ROM (compact disc with fixed memory).

The algorithm includes stages E10 to E16.

Stage E10 is a connection from the computer 7 to the database 8, via the network 9. The connection is conventional and will not be described here.

Stage E11 is the starting of the downloading of an image which has subsequently been coded as described above. As long as no data of the image has been received, an indicator is displayed in the window for displaying the image in order to indicate that.

Figure 9 represents the window 200 for displaying the image, with the region of interest ROI and the indicator-display area 201. The window 200 is displayed on the screen of the computer 7.

Obviously, the position of the region of interest is defined at coding. The position of the indicator-display area can be altered by the user.

When the data of the image reach the computer 7, stage E12 is a display of an indicator in the image-display window in order to indicate that the region of interest ROI is being received and decoded. This indicator indicates the start of the decoding of the region of interest, then the progress of the decoding thereof.

The bit planes are sent in decreasing number order and the data of the region of interest are contained in the bit planes with the highest numbers. As long as the number of the bit plane being sent is higher than or equal to 8, that corresponds to data to which the boost factor B has been applied, with B = 9 in this example. These data are those of the region of interest.

As already specified, the boost value B is used during the decoding of the data in order to transfer the boosted data B bit planes lower.

The following stage E13 is a test to check whether the region of interest ROI has been completely received and decoded. The test is carried out on the numbers of bit planes received.

As long as the response is negative, this stage is followed by the previously described stage E12.

When the response is positive at stage E13, this stage is followed by stage E14 at which an indicator is displayed in the image-display window in order to indicate that the region of interest has been completely received and consequently that its decoding is terminated.

The data not belonging to the region of interest are then being received and decoded.

The following stage E15 is a test in order to check whether the image has been completely received and decoded.

As long as the response is negative, this stage is followed by the previously described stage E14. The indicator may, moreover, display an indication of decoding of the data not belonging to the region of interest.

When the response is positive at stage E15, this stage is followed by stage E16 at which an indicator is displayed in the image-display window in order to indicate that the image has been completely received.

Clearly, the user can interrupt reception before the entire image has been received.

In a variant, the boost factor is chosen in such a way that the region of interest is not entirely "above" the rest of the signal (Figure 5), but is "slightly" emphasised by comparison with the rest of the signal. In this mode, known as scaling, the boost factor can take any value greater than or equal to one.

In this case, the coordinates of the region of interest are added as additional information to the file containing the image.

On reception, this additional information makes it possible to recover the region of interest.

Figure 10 represents an example bit plane representation, in which a boost factor equal to two has been applied to the region of interest.

The decoding of the image is similar to that described above, with the difference that the detection of the region of interest is carried out by virtue of the coordinates thereof, and no longer by analysing the dynamic range of the received signal, as in the previous example.

Clearly, the present invention is not in any way limited to the embodiments described and represented, but, on the contrary, encompasses any variant within the grasp of the person skilled in the art.

100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000